Michigan Department of Transportation 1047 (02/13)

CPM - HMA CRACK TREATMENT CURSORY INSPECTION

FOR USE WITH 12SP502(A)

INSPECTION DATE

FIELD EVALUATION OF WARRANTY PERFORMANCE CONTRACTOR **CONTROL SECTION INSPECTED BY** JOB NUMBER **REVIEWED BY ROUTE** RESIDENT ENGINEER **INSPECTION LIMITS** SAW/ROUT AND SEAL METHOD **ESTIMATED** PERCENT FAIL-SEGMENT NO. LANE DESCRIPTION COMMENTS URE (THRESHOLD LIMIT - 30%) WORK TYPE PERCENT FAILURE (SUM) **EXCEEDS THRESHOLD LIMITS** TOTAL PERCENT FAJILURES / NO. SEGMENTS (THRESHOLD LIMIT - 10%) YES NO **OVERBAND CRACK FILL METHOD ESTIMATED** PERCENT FAIL-SEGMENT NO. LANE DESCRIPTION COMMENTS URE (THRESHOLD LIMIT = 30%) WORK TYPE PERCENT FAILURE (SUM) **EXCEEDS THRESHOLD LIMITS** TOTAL PERCENT FAJILURES / NO. SEGMENTS (THRESHOLD LIMIT - 10%)