Michigan Department of Transportation 1893 (02/13)

CPM - MICROSURFACING (CURSORY INSPECTION) FIELD EVALUATION OF WARRANTY PERFORMANCE

		I ILLD LVALUATION	OI VV	AIXIXAINI I	FLINIO	KINAIACE		
CONTRACTOR				INSPECTION DATE				
CONTROL SECTION				INSPECTED BY				
JOB NUMBER				REVIEWED BY				
ROUTE				RESIDENT ENGINEER				
INSPECTION LIN	MITS							
DEBONDING				(THRES	HOLD LIN	/IT = 5% OF :	SEGMEN	IT LENGTH)
SEGMENT NO.	NO. DRIVING LANE DESCRIPTION LENGTH OF DISTRESS (FT)		FT)	DISTRESS EXCEEDS 5% OF SEGMENT LENGTH?		DISTRESS EXCEED 10% OF SEGMENT LENGTH?		COMMENTS
D-1				YES	NO	YES	NO	
D-2				YES	NO	YES	NO	
D-3				YES	NO	YES	NO	
D-4				YES	NO	YES	NO	
D-5				YES	NO	YES	NO	
RAVELING				(THRES	HOLD LIN	/IT = 8% OF	SEGMEN	IT LENGTH)
				DISTRESS E 8% OF SEC LENGT	GMENT	DISTRESS E 10% OF SE LENGT	GMENT	
RV-1				YES	NO	YES	NO	
RV-2				YES	NO	YES	NO	
RV-3				YES	NO	YES	NO	
RV-4				YES	NO	YES	NO	
RV-5				YES	NO	YES	NO	
BLEEDING/FLU	SHING			(THRES	HOLD LIN	/IT = 5% OF	SEGMEN	IT LENGTH)
				DISTRESS E 5% OF SEC LENGT	GMENT	DISTRESS E 10% OF SE LENGT	GMENT	
FL-1				YES	NO	YES	NO	
FL-2				YES	NO	YES	NO	
FL-3				YES	NO	YES	NO	
FL-4				YES	NO	YES	NO	
FL-5				YES	NO	YES	NO	
RUTTING			(THF	RESHOLD LIM	1IT 1/4")			
SEGMENT NO.	DRIVING LANE DESCRIPTION	AVERAGE RUT DEPTH FOR LEFT WHEEL PATH (IN)			GE RUT DEPTH FOR WHEEL PATH (IN)		RUT CEEDS D LIMIT?	COMMENTS
RT-1						YES	NO	
RT-2						YES	NO	